

## **INPUT**

Power supply	[50HzThree-phases+N+GND]		400V a.c.
Pneumatic pow	er (min.)	[bar]	5
Max power required (peak load)		[kW]	14

### **OUTPUT**

Upper tool weight (up to)	[up to kg]	75
Generator power	[kW]	18
Vibration frequency	[Hz]	220-245
Vibration amplitude	[mm]	0,4-1,8
PP equivalent welding area Size of the area detected in the test e	400	

### **MECHANICAL DATA**

		0.45 5.40
Vibration plate dimensions	[mm]	945×540
Lifting table stroke	[mm]	500
Lifting table maximum speed	[mm/s]	250
Clamp net force (Gross)	[kN]	18 (23,5)
Lifting table dimensions	[mm]	1400×600
Lifting table height	[mm]	1000
Front-door span	[mm]	1400×750
Upper door threshold	[mm]	1720
Clearance between planes	[mm]	700
Overall dimensions	[W×D×H mm]	2750×1250×2220
Total weight	[kg]	4500
Hydraulic oil	[Lt/IS032]	80
Machine Type		HYDRAULIC



PLC Control			Siemens S7 - CPU
HMI	Touch panel 12"		
Vibration frequency tuning <sup>2</sup>			Continuous REALTIME
Welding steps	[pressure, amplito	ude]	8
Welding depth sensit	tivity [I	mm]	0,01
Work settings memory			63 automatic equipment
Type of communication The digital generator ensures very short swing on/off vibration phases (50ms)		Profinet/Profibus	

#### **REFERENCES**

Work outcome definition		Automatic (good/reject)
Work outcome printer		Custom Plus
Vacuum circuit		I (opt. up to 3)
Pneumatic valves mover	ments	2 (opt. up to 5)
Remote-assistance		Optional
Automatic rear door (for rear loading/unloading)		Optional
Noise level	[dBA EN ISO 11202]	≤ 80

Peak values can be higher for short periods depending on the application.

The machine can be customized with some standard options, contact us for a personalized offer.





 $<sup>^{\</sup>rm I}$  Mobile table movement performed with hydraulic control unit in a dedicated area.

<sup>&</sup>lt;sup>2</sup> Thanks to our third-generation controller we have been able to eliminate the necessity of the auto-tuning cycle: the machine can adapt to the vibration frequency in real-time following the mechanical reactions of the vibrating system. Therefore, the outcome is a neater and more efficient vibration than the one obtained employing second-generation old systems.

## **UPPER PLATE**

# **LOWER PLATE**









