

## **INPUT**

Power supply	[50HzThree-phases+	N+GND]	400V a.c.
Pneumatic power	er (min.)	[bar]	5
Max power requ	uired (peak load)	[kW]	27

### **OUTPUT**

Upper tool weight (up to)	[up to kg]	120
Generator power	[kW]	18
Vibration frequency	[Hz]	220-245
Vibration amplitude	[mm]	0,4-1,8
PP equivalent welding area	[cm²]	500

### **MECHANICAL DATA**

Vibration plate dimensions	[mm]	1400×560
Lifting table stroke	[mm]	500
Lifting table maximum speed	[mm/s]	250
Clamp net force (Gross)	[kN]	17 (23,5)
Lifting table dimensions	[mm]	1700×650
Lifting table height	[mm]	1000
Front-door span	[mm]	1750×750
Upper door threshold	[mm]	1720
Clearance between planes	[mm]	700
Overall dimensions	[W×D×H mm]	3420×1310×2220
Total weight	[kg]	5200
Hydraulic oil	[Lt/IS032]	80
Machine Type		HYDRAULIC



### **CONTROL**

PLC Control			Siemens S7 - CPU
HMI			Touch panel 12"
Vibration frequency tuning <sup>2</sup>			Continuous REALTIME
Welding steps	[pressure	, amplitude]	8
Welding depth sen	sitivity	[mm]	0,01
Work settings memory			63 automatic equipment
Type of communication The digital generator ensures very short swing on/off vibration phases (50ms)		Profinet/Profibus	

#### **REFERENCES**

Work outcome definition		Automatic (good/reject)
Work outcome printer		Custom Plus
Vacuum circuit		I (opt. up to 3)
Pneumatic valves mover	ments	2 (opt. up to 5)
Remote-assistance		Optional
Automatic rear door (for rear loading/unloading)		Optional
Noise level	[dBA EN ISO 11202]	≤ 80

Peak values can be higher for short periods depending on the application.

The machine can be customized with some standard options, contact us for a personalized offer.





918ST-V21.02b

 $<sup>^{\</sup>rm I}$  Mobile table movement performed with hydraulic control unit in a dedicated area.

<sup>&</sup>lt;sup>2</sup> Thanks to our third-generation controller we have been able to eliminate the necessity of the auto-tuning cycle: the machine can adapt to the vibration frequency in real-time following the mechanical reactions of the vibrating system. Therefore, the outcome is a neater and more efficient vibration than the one obtained employing second-generation old systems.

# **UPPER PLATE**

## **LOWER PLATE**













